



- characteristics
- Double clad separation-high reliability and life expectancy ensures customer satisfaction
- Technology-to suit high temperature applications
- Appearance rugged with appealing cosmetics
- Magic Eye-for determination of electrolyte level and state-of-charge
- Easy to use batteries delivered in factory-charged, ready-to-use condition

TECHNICAL SPECIFICATIONS OF EXIDE MILEAGE RANGE OF BATTERIES												
BATTERY TYPE	PART NUMBER	REF C ₂₀ CAPACITY (Ah)	MAXIMUM OVERALL DIMENSIONS (MM)		NOMINAL FILLED WEIGHT (KG)	ELECTROLYTE VOLUME (LITRES)	CHARGING CURRENT (A)	CCA AT -18°C AS PER		ACID LEVEL INDICATOR	BATTERY LAYOUT	
			L	W	Н	(NG)			IEC	SAE		
MI32R	FMI0-MI32R	32	197	129	227	9.5	2.5	2.0	230	280	PRESENT	RIGHT LAYOUT
MI35R	FMI0-MI35R	35	197	129	227	10.4	2.2	2.5	270	332	PRESENT	RIGHT LAYOUT BB
MI35L	FMI0-MI35L	35	197	129	227	10.4	2.2	2.5	270	332	PRESENT	BE LEFT LAYOUT B
MI40LBH	FMI0-MI40LBH	35	197	137	227	10.8	2.1	3.0	280	354	PRESENT	BE LEFT LAYOUT B
MI45D21LBH	FMI0-MI45D21LBH	45	205	177	222	14.2	3.2	3.5	320	410	PRESENT	BE LEFT LAYOUT B
MI700	FMI0-MI700	65	260	173	225	18.1	4.4	4.5	400	490	PRESENT	RIGHT LAYOUT BE
MI700L	FMI0-MI700L	65	260	173	225	18.1	4.4	4.5	400	490	PRESENT	BE LEFT LAYOUT B
MI80D26R	FMI0-MI80D26R	65	260	173	225	18.1	4.4	4.5	465	582	PRESENT	RIGHT LAYOUT BE
MI105D31R	FMI0-MI105D31R	85	305	173	225	22.5	5.0	5.5	560	720	PRESENT	RIGHT LAYOUT
MI105D31L	FMI0-MI105D31L	85	305	173	225	22.5	5.0	5.5	560	720	PRESENT	BE LEFT LAYOUT B
MIDIN36(LH)	FMI0-MIDIN36(LH)	36	210	175	175	11.5	2.8	2.5	200	270	PRESENT	BET LAYOUT B
MIDIN43(LH)	FMI0-MIDIN43(LH)	43	210	175	175	13.0	2.6	3.0	265	360	PRESENT	B LEFT LAYOUT B
MIDIN44	FMI0-MIDIN44	44	207	175	190	13.0	3.0	3.0	243	360	PRESENT	BET LAYOUT B
MIDIN44R	FMI0-MIDIN44R	44	207	175	190	13.0	3.0	3.0	243	360	PRESENT	RIGHT LAYOUT BE
MIDIN50	FMI0-MIDIN50	50	207	175	190	13.9	2.9	3.5	253	405	PRESENT	BE LEFT LAYOUT BE
MIDIN55	FMI0-MIDIN55	55	242	175	190	15.7	3.6	3.5	270	420	PRESENT	BET LAYOUT B
MIDIN55R	FMI0-MIDIN55R	55	242	175	190	15.7	3.6	3.5	270	420	PRESENT	HIGHT LAYOUT
MIDIN60	FMI0-MIDIN60	60	242	175	190	16.6	3.5	4.0	320	500	PRESENT	BE LEFT LAYOUT B
MIDIN65(LH)	FMI0-MIDIN65(LH)	65	278	175	175	18.4	3.5	4.5	370	500	PRESENT	BE LEFT LAYOUT BE

MI80D26R, MI700, MI700L, MI105D31R and MI105D31L are available at 36-month warranty.

EXIDECAC1800 103 5454

When you return a used battery to any of our authorised dealers, we contribute on your behalf, to UNICEF's Child Environment Programme. It would help change the lives of the underprivileged children who are in dire need of water, sanitation and hygiene in schools. Your contribution would help save our environment as well. Lead, a major component in your battery, if not handled responsibly, can harm the environment and our health. Return your used battery and make the world a better place.



Authorised Exide Dealer

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continuous improvement and we reserve the right to change details without prior notice.

out of vehicles choose What about you?

INDIA MOVES ON **EXIDE**